

IAPMO R&T OCEANA

7-11 Fullard Road, Narre Warren, Victoria 3805, Australia



IAPMO R&T Oceana is a product certification body which inspects and arranges for the independent laboratory testing of samples taken from the manufacturer's stock or from the market or a combination of both, to verify compliance of the requirements of applicable Standards and Specifications. This activity is coupled with periodic surveillance of the manufacturer's factory and any major subcontractor's site/s as well as the assessment of the manufacturer's Quality Assurance System. This certification is subject to the conditions set forth in the characteristics below and is not to be construed as any recommendation, assurance or guarantee by IAPMO R&T Oceana of the product acceptance by Authorities Having Jurisdiction.

CERTIFICATE OF CONFORMITY

IAPMO R&T Oceana hereby grants to:

Lauxes Products Pty Ltd

A.B.N.: 84 145 485 927

16 Jade Drive, Molendinar, QLD 4214 Australia

the right to use the WaterMark in accordance with the ABCB Manual for the WaterMark Certification Scheme;– Australian Standards; WaterMark Technical Specifications; and the Plumbing Code of Australia; only in respect of the certified product as described in the WaterMark Certificate of Conformity – Schedule of Certified Product (Refer also IAPMO Product Listing Directory). The Certificate is granted subject to the rules governing the WaterMark Certification Scheme and the Terms and Conditions of the Approved User Agreement and IAPMO Oceana's WaterMark Governance Rules.

Evaluated to:

WMTS-040:2022

Waste pipe connection outlets and gratings, separate or integral

Manufacturer:

Lauxes Products Pty Ltd

Licence No.: WM-022370

First Certified: 23 August 2013

Certification Date: 15 March 2022

Expiry Date: 22 August 2024

CEO, The IAPMO Group

This WaterMark certification is for the period indicated herein and is void after the date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of IAPMO R&T Oceana, or any evidence of non-compliance with applicable Standards, Specifications or of inferior workmanship, may be deemed sufficient cause for revocation of this certification. Reproduction of or reference to this certificate for advertising purposes may be made only by specific written permission of IAPMO R&T Oceana. Any alteration of this certificate could be grounds for revocation of this certification.

"This certificate is issued by a JAS-ANZ accredited Conformity Assessment Body. The ABCB and JAS-ANZ do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The ABCB disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate."



WATERMARK CERTIFICATE OF CONFORMITY

SCHEDULE OF CERTIFIED PRODUCT



Certificate Holder

Lauxes Products Pty Ltd

A.B.N.:84 145 485 927

16 Jade Drive, Molendinar, QLD 4214 Australia

Manufacturer

Lauxes Products Pty Ltd

Standard

WMTS-040:2022

Waste pipe connection outlets and gratings, separate or integral

Licence No. WM-022370

Certification Date: 15 March 2022

Expiry Date: 22 August 2024

First Certified: 23 August 2013

Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	Outlet	Material	Additional Product Information
Lauxes	Standard Floor Grate	LCFGRATE	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. Minimum length 500mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Wide Standard Floor Grate	LCWFGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with slotted top tray. Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 35 Floor Grate	LFGNXT35	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Tile Insert Plus	LCTIGRATE	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 18mm thick. Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Standard Floor Grate	LCMFGRATE	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (black) Minimum length 500mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Wide Standard Floor Grate	LCMWFGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with slotted top tray. (black) Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 14 Floor Grate	LFGNXT14	Non plastic waste outlet	100mm (W) x 14mm (D) Aluminium anti-tracking floor grate with slotted top tray. Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 26 Floor Grate	LFGNXT26	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium anti-tracking floor grate with slotted top tray. Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange

Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	Outlet	Material	Additional Product Information
Lauxes	Midnight Next Generation 14 Floor Grate	LFGMNXT14	Non plastic waste outlet	100mm (W) x 14mm (D) Aluminium anti-tracking floor grate with slotted top tray. (black) Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Next Generation 26 Floor Grate	LFGMNXT26	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium anti-tracking floor grate with slotted top tray. (black) Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Next Generation 35 Floor Grate	LFGMNXT35	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. (black) Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert	LCSTIGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Slimline Tile Insert	LCMSTIGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (black). Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21	LCSTIGRATE21	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Slimline Tile Insert 21	LCMSTIGRATE21	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (black). Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Tile Insert Plus	LCMTIGRATE	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 18mm thick. (black) Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Matt Yellow Gold Next Generation 14 Floor Grate	LFGMYGNXT14	Non plastic waste outlet	100mm (W) x 14mm (D) Aluminium anti-tracking floor grate with slotted top tray. (matt yellow gold) Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (matt yellow gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Matt Yellow Gold Next Generation 26 Floor Grate	LFGMYGNXT26	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium anti-tracking floor grate with slotted top tray. (matt yellow gold) Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (matt yellow gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Matt Yellow Gold Slimline Tile Insert	LCMYGSTIGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (matt yellow gold). Minimum length 500mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (matt yellow gold)	To be installed within a WaterMark certified puddle flange

END RECORD

END RECORD


 CEO, The IAPMO Group