


## PRODUCT SPECIFICATIONS

<b>Product</b>	Storm Water Tile Insert (SWT128)
<b>Code</b>	SWT128-M-5.6
<b>Colour</b>	Midnight
<b>Length</b>	5600mm
<b>Width</b>	128mm
<b>Depth</b>	19mm (Top Only)
<b>Material</b>	Anodised Aluminium
<b>Weight</b>	13.0kg per full length
<b>Applications</b>	Outdoor
<b>Features</b>	<ul style="list-style-type: none"> <li>• Sleek Design</li> <li>• Easy Installation</li> <li>• High Water Flow</li> <li>• Suitable for tiles up to 13mm thick</li> <li>• Lifetime Rustproof Warranty</li> <li>• UV Stable</li> <li>• Replacement Top Only</li> </ul>
<b>Load Rating</b>	Class B - Maximum Load at 10.2 tons



\* Total length of full grate is 5.8m, total usable length is 5.6m to allow for any wastage during the anodising process.

\* Regular, gentle cleaning with soapy water is recommended. Do not use abrasive cloths or acidic chemicals on the grates.

## CUTTING INSTRUCTIONS AND INSTALLATION

For ease of cutting Lauxes grates, we recommend using a compound mitre saw fitted with a multi-material cutting blade 80 tooth or more.

1. Cut your Lauxes grate to the desired length.
2. Remove existing plastic top tray.
3. Replace with new Lauxes Storm Water top tray.

\* During installation ensure the grate does not come in contact with any wet cement based products.

\* When installing tile, use a neutral cure silicone.

