


# IAPMO OCEANIA

7-11 Fullard Road, Narre Warren, Victoria 3805, Australia /info@lapmoceania.org



## CERTIFICATE OF CONFORMITY

*IAPMO Oceania hereby grants to:*

### **Lauxes Products Pty Ltd**

16 Jade Drive, Molendinar, QLD 4214 Australia

Email: [hello@lauxesproducts.com.au](mailto:hello@lauxesproducts.com.au)

the right to use the WaterMark in accordance with the ABCB Manual for the WaterMark Certification Scheme;– Australian Standards; WaterMark Technical Specifications; and the Plumbing Code of Australia; only in respect of the certified product as described in the WaterMark Certificate of Conformity – Schedule of Certified Product (Refer also IAPMO Product Listing Directory). The Certificate is granted subject to the rules governing the WaterMark Certification Scheme and the Terms and Conditions of the Approved User Agreement and IAPMO Oceania's WaterMark Governance Rules.

*Evaluated to:*

**WMTS-040:2022**

Waste pipe connection outlets and gratings, separate or integral

*Manufacturer:*

Refer to Licence Holder

**Licence No.:** WM-022370

**First Certified:** 23 Aug 2013

**Certification Date:** 23 Jan 2026

**Expiry Date:** 22 Aug 2029

A handwritten signature in blue ink that reads 'David Viola'.

David Viola

Chief Executive Officer of the IAPMO Group

This WaterMark certification is for the period indicated herein and is void after the date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of IAPMO Oceania, or any evidence of non-compliance with applicable Standards, Specifications or of inferior workmanship, may be deemed sufficient cause for revocation of this certification. Reproduction of or reference to this certificate for advertising purposes may be made only by specific written permission of IAPMO Oceania. This certificate can only be reproduced in its entirety. Any alteration of this certificate could be grounds for revocation of this certification.

"This certificate is issued by a JAS-ANZ accredited Conformity Assessment Body. The ABCB and JAS-ANZ do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The ABCB disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate."



# WATERMARK CERTIFICATE OF CONFORMITY

## SCHEDULE OF CERTIFIED PRODUCT



*Certificate Holder*

**Lauxes Products Pty Ltd**

A.B.N.:

16 Jade Drive, Molendinar, QLD 4214 Australia

*Manufacturer*

**Refer to Licence Holder**

*Standard*

**WMTS-040:2022**

Waste pipe connection outlets and gratings, separate or integral

**Licence No. WM-022370**

**Certification Date: 23 Jan 2026**

**Expiry Date: 22 Aug 2029**

**First Certified: 23 Aug 2013**

Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	Outlet	Material	Additional Product Information
Lauxes	Standard Floor Grate	LCFGRATE	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Wide Standard Floor Grate	LCWFGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with slotted top tray. Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Tile Insert Plus	LCTIGRATE	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 18mm thick. Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Standard Floor Grate	LCMFGRATE	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (black) Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Wide Standard Floor Grate	LCMWFGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with slotted top tray. (black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 14 Floor Grate	LFGNXT14	Non plastic waste outlet	100mm (W) x 14mm (D) Aluminium anti-tracking floor grate with slotted top tray. Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 26 Floor Grate	LFGNXT26	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium anti-tracking floor grate with slotted top tray. Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 35 Floor Grate	LFGNXT35	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Next Generation 14 Floor Grate	LFGMNXT14	Non plastic waste outlet	100mm (W) x 14mm (D) Aluminium anti-tracking floor grate with slotted top tray. (black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Next Generation 26 Floor Grate	LFGMNXT26	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium anti-tracking floor grate with slotted top tray. (black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Next Generation 35 Floor Grate	LFGMNXT35	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. (black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange

Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	Outlet	Material	Additional Product Information
Lauxes	Slimline Tile Insert	LCSTIGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Slimline Tile Insert	LCMSTIGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (black). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21	LCSTIGRATE21	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Slimline Tile Insert 21	LCMSTIGRATE21	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (black). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Midnight Tile Insert Plus	LCMTIGRATE	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 18mm thick. (black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (black)	To be installed within a WaterMark certified puddle flange
Lauxes	Matt Yellow Gold Next Generation 14 Floor Grate	LFGMYGNXT14	Non plastic waste outlet	100mm (W) x 14mm (D) Aluminium anti-tracking floor grate with slotted top tray. (matt yellow gold) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (matt yellow gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Matt Yellow Gold Next Generation 26 Floor Grate	LFGMYGNXT26	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium anti-tracking floor grate with slotted top tray. (matt yellow gold) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (matt yellow gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Matt Yellow Gold Slimline Tile Insert	LCMYGSTIGRATE	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (matt yellow gold). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (matt yellow gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Standard Floor Grate 23 - Silver	SFG23-S-5.6	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (Silver) Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (Silver)	To be installed within a WaterMark certified puddle flange
Lauxes	Standard Floor Grate 23 - Midnight	SFG23-M-5.6	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (Black) Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (Black)	To be installed within a WaterMark certified puddle flange
Lauxes	Standard Floor Grate 23 - Gold	SFG23-G-5.6	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (Gold) Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (Gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Standard Floor Grate 23 - Brushed Nickel	SFG23-BN-5.6	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (Brushed Nickel) Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (Brushed Nickel)	To be installed within a WaterMark certified puddle flange
Lauxes	Standard Floor Grate 23 - Gun Metal	SFG23-GM-5.6	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (Gun Metal) Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (Gun Metal)	To be installed within a WaterMark certified puddle flange
Lauxes	Standard Floor Grate 23 - Copper	SFG23-C-5.6	Non plastic waste outlet	70mm (W) x 23mm (D) Aluminium floor grate with slotted top tray. (Copper) Minimum length 70mm.	Shower	DN 50	40mm or 50mm plain spigot	Anodised aluminium alloy (Copper)	To be installed within a WaterMark certified puddle flange
Lauxes	Wide Standard Floor Grate 26 - Silver	WSFG26-S-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with slotted top tray. (Silver) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Silver)	To be installed within a WaterMark certified puddle flange
Lauxes	Wide Standard Floor Grate 26 - Midnight	WSFG26-M-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with slotted top tray. (Black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Black)	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 14 - Silver	NXT14-S-5.6	Non plastic waste outlet	100mm (W) x 14mm (D) Aluminium anti-tracking floor grate with slotted top tray. (Silver) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Silver)	To be installed within a WaterMark certified puddle flange



Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	Outlet	Material	Additional Product Information
Lauxes	Next Generation 35 - Midnight	NXT35-M-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. (Black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Black)	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 35 - Gold	NXT35-G-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. (Gold) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 35 - Brushed Nickel	NXT35-BN-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. (Brushed Nickel ) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Brushed Nickel)	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 35 - Gun Metal	NXT35-GM-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. (Gun Metal) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gun Metal)	To be installed within a WaterMark certified puddle flange
Lauxes	Next Generation 35 - Copper	NXT35-C-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium anti-tracking floor grate with slotted top tray. (Copper) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Copper)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21 - Silver	STI21-S-5.6	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (Silver) Minimum length 100mm.	Shower	DN90	72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Silver)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21 - Midnight	STI21-M-5.6	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (Black). Minimum length 100mm.	Shower	DN90	72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Black)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21 - Gold	STI21-G-5.6	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (Gold). Minimum length 100mm.	Shower	DN90	72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21 - Brushed Nickel	STI21-BN-5.6	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (Brushed Nickel). Minimum length 100mm.	Shower	DN90	72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Brushed Nickel)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21 - Gun Metal	STI21-GM-5.6	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (Gun Metal). Minimum length 100mm.	Shower	DN90	72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gun Metal)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 21 - Copper	STI21-C-5.6	Non plastic waste outlet	100mm (W) x 21mm (D) Aluminium floor grate with insert. Holds tile up to 10mm thick. (Copper). Minimum length 100mm.	Shower	DN90	72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Copper)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 26 - Silver	STI26-S-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (Silver) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Silver)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 26 - Midnight	STI26-M-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (Black). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Black)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 26 - Gold	STI26-G-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (Gold). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 26 - Brushed Nickel	STI26-BN-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (Brushed Nickel). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Brushed Nickel)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 26 - Gun Metal	STI26-GM-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (Gun Metal). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gun Metal)	To be installed within a WaterMark certified puddle flange
Lauxes	Slimline Tile Insert 26 - Copper	STI26-C-5.6	Non plastic waste outlet	100mm (W) x 26mm (D) Aluminium floor grate with insert. Holds tile up to 11mm thick. (Copper). Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Copper)	To be installed within a WaterMark certified puddle flange

Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	Outlet	Material	Additional Product Information
Lauxes	Tile Insert Plus 35 - Silver	TIP35-S-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 20mm thick. (Silver) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Silver)	To be installed within a WaterMark certified puddle flange
Lauxes	Tile Insert Plus 35 - Midnight	TIP35-M-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 20mm thick. (Black) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Black)	To be installed within a WaterMark certified puddle flange
Lauxes	Tile Insert Plus 35 - Gold	TIP35-G-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 20mm thick. (Gold) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gold)	To be installed within a WaterMark certified puddle flange
Lauxes	Tile Insert Plus 35 - Brushed Nickel	TIP35-BN-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 20mm thick. (Brushed Nickel ) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Brushed Nickel )	To be installed within a WaterMark certified puddle flange
Lauxes	Tile Insert Plus 35 - Gun Metal	TIP35-GM-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 20mm thick. (Gun Metal) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Gun Metal)	To be installed within a WaterMark certified puddle flange
Lauxes	Tile Insert Plus 35 - Copper	TIP35-C-5.6	Non plastic waste outlet	100mm (W) x 35mm (D) Aluminium floor grate with insert. Holds tile up to 20mm thick. (Copper) Minimum length 100mm.	Shower	DN90	40mm, 50mm, 72mm, 80mm or 90mm plain spigot	Anodised aluminium alloy (Copper)	To be installed within a WaterMark certified puddle flange

---

**END RECORD**

**END RECORD**

---



David Viola  
Chief Executive Officer of the IAPMO Group